

Ratho-Intern 12/00/1

„5-Kanal-Endstufe in SMD-Technologie!“

SD-700



Features

- ▶ SMD Technologie
- ▶ Vergoldete Terminals
- ▶ regelbarer Tief/Hochpass 20Hz - 5KHz
- ▶ regelbarer Tief/Hochpass 20Hz - 500Hz für Kanal 5
- ▶ regelbarer Bassboost 0 - 12dB
- ▶ SMD Technology
- ▶ Golden Terminals
- ▶ adjustable High/Low 20Hz - 5KHz
- ▶ adjustable Lowpass 20Hz - 500Hz for Channel 5
- ▶ adjustable Bassboost 0-12dB

Technische Daten / Specifications

RMS Leistung/ RMS Power	4 x 75W + 1 x 200W
max. Leistung/ max. Power	4 x 150W + 1 x 400W
Leistung gebrückt/Bridged Power max.	2 x 300W + 1 x 400W
THD	0,05%
Frequenzgang / Frequency response	14Hz-30KHz
S/N Ratio	90dB
Maße/Dimensions (mm)	294x56,5x405



Amplificateur de 5 canaux avec SMD Technologie



RATHO
Electronic Vertriebs-GmbH

Burchardstraße 6 • 20095 Hamburg
Tel.: 040/325446-0
Fax: 040/32544632
E-Mail: Ratho@t-online.de
Internet: www.ratho.com

Impulse USAcoustics Amplifier Series